

A proven performer for trailer loading and unloading. Ideally suited for packaging, shipping and flexible assembly lines. Order optional leg connect brackets to lock units together.

- **Structural Steel Support:** Channel steel spans the entire conveyor width for unequalled strength.
- **1-1/4" Side Plates:** Aluminum alloy with ribbed construction for added durability. Assembled with shoulder bolts.



Model Number	Width	Compacted to Expanded	Conveyor Height	Leg Sets Per Unit	Wheels Per Axle	Unit Weight
FX200-18-12-ST-5	18 in.	3 ft. to 12 ft.	28 1/2" to 41 1/2"	4	7	215 lbs.
FX200-18-24-ST-5	18 in.	6 ft. to 24 ft.	28 1/2" to 41 1/2"	7	7	429 lbs.
FX200-24-12-ST-5	24 in.	3 ft. to 12 ft.	28 1/2" to 41 1/2"	4	9	252 lbs.
FX200-24-24-ST-5	24 in.	6 ft. to 24 ft.	28 1/2" to 41 1/2"	7	9	504 lbs.

**24 HOUR SHIPMENT SUBJECT TO AVAILABLE STOCK
24 HOUR SHIPMENT NOT GUARANTEED.**

• Standard Specifications

WIDTHS-18 in. and 24 in.

FRAME-Flexible and extendible.

LENGTHS-12 ft. and 24 ft.

EXPANSION RATIO-4:1

FLOOR SUPPORTS-Adjustable type 28-1/2" to 41-1/2".

WHEELS-1.9 in. dia. with 1/4 in. bore.


PACKAGE STOP-Folds down when not in use.

CASTERS-Swivel casters with locking brake.

CAPACITY- 200 lbs. capacity per linear foot.

• Optional Equipment

LEG CONNECT BRACKETS-Connecting two or more conveyors.



LEG CONNECT BRACKETS

GRAVITY