

MQ Series

Manual Quad Drive Carton Sealer

The BestPack™ MQ Series is designed to effectively fulfill heavy-duty and unstable sealing needs. Featuring a quad-belt drive, two on the side and two on the top, the MQ series will securely pull through unstable cartons and is powered by three 110V UL-approved electric motors. The mast allows for an extra 4" carton height extension on the upper assembly.

Our MQ line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

Features

- Designed for Uniform Applications
- Fully Adjustable
- Four Belt Drive - 2 Top & 2 Side
- Adjustable Bed Height for the MQ Type Sealers: 20.5" to 30"
- Electrical On/Off Box can be Mounted on Either Side of Carton Sealer
- Width/Height Adjustment on Either Side of Carton Sealer
- Upper Side Compression Unit
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Heavy-Duty Locking Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Motorized Height and/or Width Adjustment
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Food Grade 304 Stainless Steel
- Short Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 50 Cartons/min.
Speed

None
Air Requirements

385 - 600 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
MQ22-2 or 22-3 2" or 3" Tape Head	(39.5") x (36.0") x (55.5")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 20.5")	(20.5" - 30.0")	Up to 40	385
MQ22-2H** or 22-3H** 2" or 3" Tape Head	(39.5") x (36.0") x (55.5")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 20.5")	(20.5" - 30.0")	Up to 50	385
MQ23-2 or 23-3 2" or 3" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 30.0")	(20.5" - 30.0")	Up to 40	420
MQ23-3H** or 23-3H** 2" or 3" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 30.0")	(20.5" - 30.0")	Up to 50	420
MQ33-3 3" Tape Head	(39.5") x (43.0") x (81.0")	(6.0" - U) x (7.5" - 30.0") x (6.0" - 30.0")	(20.5" - 30.0")	Up to 25	542
MQ33-3H** 3" Tape Head	(39.5") x (43.0") x (81.0")	(6.0" - U) x (7.5" - 30.0") x (6.0" - 30.0")	(20.5" - 30.0")	Up to 32	542
MQ44-3 3" Tape Head	(39.5") x (53.0") x (91.0")	(6.0" - U) x (7.5" - 40.0") x (6.0" - 40.0")	(20.5" - 30.0")	Up to 25	600
MQ44-3H** 3" Tape Head	(39.5") x (53.0") x (91.0")	(6.0" - U) x (7.5" - 40.0") x (6.0" - 40.0")	(20.5" - 30.0")	Up to 32	600

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
** High Speed